



# E200G4



## High Efficiency Edge AIoT Box

### Highlights

- **Outstanding Computing Capability for AI and Edge Applications**
- **Great Flexibility with Multiple Wireless/AI Modules**
- **Industrial-Level Rugged Embedded System with Wide Operating Temperature Range**

### Enhanced Performance and High Efficiency

E200G4, a high efficiency AIoT Box system based on 10nm 11th Gen Intel® Core™ Processor, delivers balanced performance (up to 23% gain in single-thread performance and up to 19% gain in multi-thread performance). E200G4 not only incorporates Intel® Iris® Xe graphics that achieves up to 2.95x graphic capability, but also offers 1x PCIe Gen4 x4 slot and 2x DDR4 SODIMM slots with In-Band ECC. E200G4 is an ideal uCPE or edge platform for integrated AI acceleration, plus capabilities for applications that demand high-speed processing, computer vision, and low-latency deterministic computing.

### Flexible Network Configuration

E200G4 provides multiple internal M.2 expansion slots and wireless modules, supporting 4G LTE or 5G NR (Sub 6G) and WiFi-6 modules for IoT applications or SSD NVMe module for general storage. Moreover, E200G4 features high bandwidth network communication capabilities which can cater to suitable demands of different application procedures.



Edge AIoT



5G/WiFi6/  
LoRa wireless  
connections



Media & AI  
Integration



Modulation  
Design to  
support  
difference IoT  
scenario

Front View



Rear View



## Satisfactory Stability and Easy Serviceability

Designed with a highly modular architecture in ultra-thin form factor, it is easy to service and maintain. Meanwhile, features like wide operating temperature range and strong environmental adaptability make E200G4 perfect for various applications including intelligent video surveillance, big data analysis, industry 4.0, intelligent healthcare industry and more.

## High-Performance 5G Fixed Wireless Access

E200G4 supports Fixed Wireless Access (FWA) technology that delivers 5G/LTE broadband services to residential subscribers and enterprise customers. E200G4 is Microsoft Azure certified device, which allows for quick and efficient deployment as an edge device for Microsoft cloud services.

## A New Software-Driven Platform

Furthermore, Inventec collaborates with Canonical to provide a software and hardware integration solution. E200G4 adopts Ubuntu Linux operation system (OS) and possesses access to the Inventec Store, which is an app store platform from Canonical, with full control over the store content, review process and identity to provide users with more secure and reliable services. E200G4 can also become an NFVI (Network Functions Virtualization Infrastructure) platform by running Canonical's open source NFV stack, designed for hosting VNFs with optimum performance and security requirements.

## About Inventec Data Center Solutions (Inventec EBG)

Inventec Data Center Solutions (Inventec EBG) was established in 1998 and has been focusing on the design and manufacturing of server systems in Inventec Corporation. Over decades, Inventec EBG has been the key server system supplier of the global branding clients.

# E200G4 | Edge AIoT Box

<b>Positioning</b>	Edge AIoT (uCPE)
<b>Form Factor</b>	W x H x D: 220mm x 42.1mm x 172mm (8.66 x 1.66 x 6.77 inch)
<b>Processor</b>	11 <sup>th</sup> Gen Intel® Core™ Processor Up to 4 Processor Cores, 2-4MB Cache TDP up to 15W
<b>Memory Slot</b>	2 DDR4 channels, 2666/3200 MT/s, Max. 64GB In-Band ECC
<b>Expansion Slot</b>	2x M.2 slots support AI & NVMe module (AI module supports dual or single M.2 accelerator module) 1x M.2 slot supports NVMe & LoRa module 1x M.2 slot supports WiFi/BT module 1x M.2 slot supports 4G LTE/5G NR module
<b>I/O Interface</b>	2x RJ45 2.5G with TSN 1x COM port & 1x RS485 2x USB 3.2 port & 2x USB2.0 port 1x HDMI 2.0 port
<b>Networking</b>	Dual-WAN (5G & Ethernet) with Load Balancing and Failover IPv4 / IPv6 routing NAT / NATP DHCP Server & Client
<b>System Management</b>	LWM2M Client, to be managed by OMAcompliant device management system Device Twin Zero Touch Provisioning OTA Logs & tracing
<b>Security</b>	Firewall IPsec VPN
<b>TPM</b>	Supports TPM2.0 (Option)
<b>Antenna</b>	6x external antennas
<b>Fan</b>	Fan less
<b>Power Supply</b>	Power adapter 12V/8A, 96W
<b>Mounting</b>	Standard/Wall Mount
<b>Environmental</b>	Operating Temperature: -20°C~60°C (0.7m/s air flow) IP Ratings (Ingress Protection): IP51 Vibration During Operation: IEC 60068-2-64 Shock During Operation: IEC 60068-2-27

## Inventec Corporation (TAO)

No.88, Dazhi Rd., Taoyuan Dist., Taoyuan City 33068, Taiwan  
Tel: 886-3-390-0000 Fax: 886-3-376-2370  
Email: TAOproductsupport@inventec.com

Learn more at <https://ebg.inventec.com/>

